


Job name:	Date:
Scheduled Reference:	Contractor:

System information



AHRI number	\	
Outdoor Model	\	WLW09HQ19SDO
Indoor Model	\	WLW09HQ19SDI
System Rating		
Cooling Capacity	Btu/h	9100
Heating Capacity (47°F)	Btu/h	10000
Heating Capacity (17°F)	Btu/h	6000
Cooling Capacity Range	Btu/h	2800-10300
Heating Capacity Range	Btu/h	2200-12200
Power Supply	\	208-230V/1Ph/60Hz
SEER2	\	19.5
HSPF2	\	8.8
EER	W/W	3.3
COP	W/W	3.7
Gas Pipe	inch (mm)	3/8 (9.52)
Liquid Pipe	inch (mm)	1/4 (6)
Pre-Charge Length	ft (M)	24.6 (7.5)
MIN. Refrigerant Pipe Length	ft (M)	10 (3)
MAX. Refrigerant Pipe Length	ft (M)	100 (30)
MAX. Vertical Height difference between Indoor and Outdoor	ft (M)	66 (20)
Connection Method	\	Screw Connection
Refrigerant Type	\	R410A
Factory Charge	oz	24.7
Additional Charge	oz	0.2


Features:

- Wi-fi
- 8C heating mode
- I-feel function
- Turbo mode
- Self-clean function
- Dehumidify



Outdoor Data and Dimensions

Outdoor Unit Data		
Compressor Type		Rotary
Compressor RLA	A	5.2
Sound Pressure Level	dB(A)	51
Min/Max Voltage	V	187-253
MCA	A	9
MOP	A	15
Dimension (HxWxD)	inch (mm)	21 27/32 x 28 13/16 X 12 63/64 (555 x 732 x 330)
Net Weight	lb (Kg)	56.2 (25.5)
Gross Weight	lb (Kg)	61.7 (28)
Operating Temperature for Cooling	°F/°C	0-118 (-18-48)
Operating Temperature for Heating	°F/°C	-13-75 (-25-24)



Indoor data and Dimensions

Indoor Unit Data		
Air Flow Volume	CFM (m ³ /h)	158-353 (270-600)
Sound Pressure Level	dB(A)	26-41
Dehumidification	pt/hr	1.69
Min/Max Voltage	V	187-253
MCA	A	-
MOP	A	-
Dimension (HxWxD)	inch (mm)	10 55/64 x 34 9/64 x 8 7/64 (276 x 867 x 206)
Net Weight	lb (Kg)	20.9 (9.5)
Gross Weight	lb (Kg)	25.4 (11.5)

Unit: inch

W	H	D	W1	W2	W3
34 9/64	10 55/64	8 7/64	7 43/64	18 3/16	8 17/64

